

RAY - KSK 4000 MCR

Coordinate grinding head KSK 4000 MCR

For internal grinding of bores and slots into an exact measurement.

| | | |
|-----------|-----------------------|---------------------|
| Capacity: | bore-diameter | max. 310 mm / 12.2" |
| | bore-depth | max. 250 mm / 9.84" |
| Accuracy: | 0.001 mm / 0.0000393" | |

Consisting of:

- 1 Standard fixing cone size 3
- 1 Intermediate cable
- 1 Diamond device
- 1 Socket key 5 mm
- 1 Instruction book
- 1 Meter for circumferential speed
- 1 Warranty certificate
- 1 Wooden case 4000
- 1 Control unit ADIM II MCR with:
 - input voltage 1x 115/230V
 - adjustable from 6'000 – 99'000 r.p.m.
- 1 Mains connector
- 1 Control cable
- 1 Remot control ADIM REMOTE incl. connection cable
- 1 ELTA-holding device

Price KSK 4000 MCR complete

US\$ 52,850.00

| |
|--------------------|
| RAY - KSK 4000 MCR |
|--------------------|

Accessories:

| Description | Specification | Price US\$ |
|--------------------------------------|---|------------|
| High frequency spindle R 250 | 6'000 – 15'000 r.p.m., 1000 Watt incl. holding device for grinding wheel flange | 9,787.00 |
| Wheel flange | bore Ø 20 mm (for R 250) | 879.00 |
| Spindle prolonging device T 150 | (for R 250) | 5,422.00 |
| Standard fixing cones (1 size incl.) | ISO 45 | 925.00 |
| | ISO 50 | 925.00 |
| | MK 5 | 890.00 |
| | BT 45 | 1,110.00 |
| | BT 50 | 1,110.00 |
| High frequency spindle R 170 | 15'000 – 40'000 r.p.m., 500 Watt for collet holding, incl. collet nut EX16 | 8,520.00 |
| Collets EX16 | Ø 1 - Ø 10 mm | Ea. 95.00 |
| Balancing instrument | „SKF Vibration Pen“ | 4,071.00 |

Terms and Conditions of Sales

Price: F.O.B Novatech Scottsdale AZ 85260, USA
Payment: 10% with order, balance prior shipment
Warranty: 12 months
Weight: Approx. 15 kg / 33.3 lbs. net
Delivery: Approx. 4 weeks after date of order
Installation: Coordinate grinding head KSK 4000 MCR can be installed with
 In-house staff

TECHNICAL SPECIFICATIONS AND PRICE SUBJECT TO CHANGE WITHOUT NOTICE